

QUOTATION


(618) 624-8340 TEL
 8670 US Hwy 50
 Lebanon, IL 62254

Quote Number:	Date:
QCB CELL 121619	12/16/2019

ORGANIZATION	Franklin County Govt.	PHONE
CONTACT	Randall Crocker	FAX
ADDRESS		EMAIL
CITY /STATE / ZIP	Benton, IL	
TYPE WORK	Cellular Repeater for the Basement of the Campbell Building	

QTY	PART NUMBER	DESCRIPTION	EACH	TOTAL
Cellular Repeater				
1	SC-FUSION5X2-04D	Cell signal repeater kit, w/ 4 indoor domes & 1 outdoor omni, SureCall	1356.03	1356.03
1	SC-LP	Lightning protector, SureCall	58.08	58.08
0.5	LOW-400P-OR-D	Wire, LMR-400 coax, plenum, 1000', Times Microwave	2340.00	1170.00
20	SC-CN-9	Connector, N-Type, for LMR400 plenum, SureCall	7.08	141.60
1	LABOR	Install J-Hooks, cables, antennas, and amplifier. Test operation.	1694.00	1694.00
Supplies				
1	JM	Misc material (J-Hooks, hardware, etc.)	14.45	14.45
			SUB TOTAL	4434.16

ETA	TBD	EXPIRES	1/15/2020	FREIGHT	43.84
TERMS	NET 30	SHIP VIA	GROUND	TAX	N/A
REP.	Bill Crocker	PAGE	1 of 1	TOTAL	4478.00
SIGNED	<i>Bill Crocker</i>	Accepted By:	<i>Randall Crocker</i>		



FUSION5X™ 2.0



Voice &
4G LTE



Most
powerful



All major
carriers



Auto-
Adjusting

SureCall Fusion5X 2.0 with Auto Adjusting Gain

All-Carrier Cellular Signal Booster Provides Max Connectivity

Overview

Fusion5X 2.0 is the industry's most powerful cellular signal booster in its class. Covering up to 2X more area than the closest competitor, Fusion5X 2.0 is the chosen solution for mid- to large-size applications that need access to reliable voice, text, and data signals. The Fusion5X 2.0 works with all phones and mobile devices on all North American cellular networks.


Features & Benefits

- +16 dBm downlink power for 2X more coverage area than the competition
- Improves voice, text and 4G LTE data signals in mid- to large-size buildings, offices and residences
- Built in SureIQ™ technology eliminates shut-down caused by overpowering and replaces attenuators to deliver 24/7 uptime
- Auto-adjusting gain ensures continuously maximized performance
- Supports all North American phones and cellular networks
- Industry best 3-year warranty and lifetime, US-based tech support
- Compatible with SureCall Sentry™ for remote monitoring

Standard Kit Options:

All kits ship complete with indoor and outdoor antennas and low-loss coax cables

Model number	Model name	Outside Antenna	Inside Antenna(s)
SC-Fusion5X2-OD	Fusion5X 2.0 Omni / Dome Kit	(1) Omni	(1) Dome
SC-Fusion5X2-O4D	Fusion5X 2.0 Omni / 4 Dome Kit	(1) Omni	(4) Dome
SC-Fusion5X2-OP	Fusion5X 2.0 Omni / Panel Kit	(1) Omni	(1) Panel
SC-Fusion5X2-O4P	Fusion5X 2.0 Omni / 4 Panel Kit	(1) Omni	(4) Panel
SC-Fusion5X2-YD	Fusion5X 2.0 Yagi / Dome Kit	(1) Yagi	(1) Dome
SC-Fusion5X2-Y4D	Fusion5X 2.0 Yagi / 4 Dome Kit	(1) Yagi	(4) Dome
SC-Fusion5X2-YP	Fusion5X 2.0 Yagi / Panel Kit	(1) Yagi	(1) Panel
SC-Fusion5X2-Y4P	Fusion5X 2.0 Yagi / 4 Panel Kit	(1) Yagi	(4) Panel



Shown: Fusion5X 2.0 Omni / 4 Dome Kit
SC-Fusion5X2-O4D

Key Product Specifications

- Uplink: 698–716 / 776–787 / 824–849 /
- Frequency Range: 1850–1915 / 1710–1755 MHz
- Downlink: 728–746 / 746–757 / 869–894 /
- Frequency Range: 1930–1995 / 2110–2155 MHz
- Supported Standards: CDMA, WCDMA, GSM, EDGE, HSPA+, EVDO, 4G and all cellular standards
- Max Gain: 72 dB
- Downlink Power: +16 dBm
- Noise Figure: 8 dB
- Max Output Power: 1 Watt EIRP
- RF Connectors: N Female (both ends)
- Power Consumption: <25W

